

QUALITY ENABLES.

Case study on municipal water treatment in Ford City, Pennsylvania, USA

QUALITY WORKS.

LANXESS
Energizing Chemistry

Drinking water production at municipal water treatment plant – combining IX and RO leads to superior results

Application and system design

The Ford City, Pennsylvania municipal water treatment plant has been providing water for residential purposes since 1920 using conventional chemical treatment methods. In 2015, the plant identified a need for a new system that would bring total dissolved solids (TDS) below 375 mg/l and hardness (Mg, Ca concentration) below 175 mg/l.

The resulting new water treatment facility consists of a water softening stage using ion exchange (IX) technology paired with a reverse osmosis (RO) system using **Lewabrane® RO B400 LE ASD** membranes to meet TDS requirements. The softening removes the carbonate hardness before the effluent is split into two streams. One stream is fed to the RO system, and the other blended with the RO permeate. The treated water goes into a storage tank with a capacity of 1.5 million gallons (5,680 m³). To prevent scaling formed by sulfates, antiscalant is continuously added to the reverse osmosis influent. This is essential to achieving the requested high recovery rate without the danger of salt precipitation. Lastly, chlorination is used as a final disinfectant step for the treated water.

At a glance

Application	Drinking water production
Location	Pennsylvania, USA
Product	Lewabrane® RO B400 LE ASD
Number of elements	60 pieces
Production capacity	270 GPM (61.3 m ³ /h)
Water type	Brackish well (SDI <5)
Installation	2017

Membrane performance

The Ford City RO system was designed using the **LewaPlus®** design projection software, modelling both the WAC (weak acid cation) softening step and the split stream RO step. The RO system design was optimized with two stages utilizing a 7–3 array, with six membranes in each pressure vessel, operating at a recovery rate of 82%. The RO system has an overall permeate flow rate of 270 GPM (61.3 m³/h). This permeate is blended with softened city water at 170 GPM (38.6 m³/h), yielding a finished, treated water stream of 440 GPM (100 m³/h). The plant has two RO systems, which alternate in operation on a day-to-day basis.

The current Lewabrane® RO B400 LE ASD elements were installed in September 2017 and have been running at a steady state with no major issues. The RO system has been functioning properly, maintaining a 16.2 gfd (27.6 l/m²h) average operating flux, and an 82% recovery rate. No significant increases in feed pressure have been observed since start-up.


The Lewabrane® RO B400 LE ASD membrane element is prepared with an innovative 34 mil feed spacer, designated ASD, for alternating strand design. This novel feed spacer technology offers alternating thick-thin strands, increasing feed channel porosity and reducing dormant flow areas. It has been proven to lower biofouling and reduce feed pressure buildup. The ASD spacer is highly recommended for municipal applications where biofouling may become an issue.

Conclusion

The Lewabrane® RO B400 LE ASD membrane elements installed at the Ford City plant have consistently performed within the desired parameters with no significant scaling or fouling observed since the September 2017 start-up. Due to the combined process, a high recovery rate of 82% has been maintained with a high water quality, which is meeting the clients requirements.

The Ford City operating staff are very pleased with the IX and RO system performance.

Ford City municipal plant system diagram



We will be happy to support your business. Please contact us for additional information: visit www.lpt.lanxess.com

LANXESS
Energizing Chemistry

LANXESS Deutschland GmbH
Liquid Purification Technologies
Kennedyplatz 1
50569 Cologne, Germany
Phone: +49 221 8885-0
E-mail: lewabrane@lanxess.com

Health and Safety Information: Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling the LANXESS products mentioned in this publication. For materials mentioned which are not LANXESS products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be followed. Before working with any of these products, you must read and become familiar with the available information on their hazards, proper use and handling. This cannot be overemphasized. Information is available in several forms, e.g., material safety data sheets, product information and product labels. Consult your LANXESS representative in Germany or contact the Health, Safety, Environment and Quality Department (HSEQ) of LANXESS Germany or - for business in the USA - the LANXESS Product Safety and Regulatory Affairs Department in Pittsburgh, PA.

Regulatory Compliance Information: Some of the end uses of the products described in this publication must comply with applicable regulations, such as the FDA, BIR, NSF, USDA, and CPSC. If you have any questions on the regulatory status of these products, contact your LANXESS Corporation representative, the LANXESS Regulatory Affairs Manager in Pittsburgh, PA or the Health, Safety, Environment and Quality Department (HSEQ) of LANXESS Deutschland GmbH in Germany. The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

All trademarks are trademarks of the LANXESS Group, unless otherwise specified. Status 02/2020.